

# T O HJ

Screw-in socket, T shaped

**HANSA FLEX**

## Properties

**Connection 1** UN/UNF external threads

**Sealing form 1** O-ring seal on screw-in socket

**Connection 2 + 3** UN/UNF external threads


**Sealing form 2 + 3** 74° outer cone

**Design** Adjustable direction screw-in socket

**Construction** T shaped

**Material** Steel

**Surface** electro galvanised



## Item

Identification	G1	G2 + G3	AF (mm)	S1	OR
T O 04 HJ	7/16"-20 UNF	7/16"-20 UNF	11	14	8.92 x 1.83
T O 05 HJ	1/2"-20 UNF	1/2"-20 UNF	14	16	10.52 x 1.83
T O 06 HJ	9/16"-18 UNF	9/16"-18 UNF	14	17	11.90 x 1.98
T O 08 HJ	3/4"-16 UNF	3/4"-16 UNF	19	22	16.36 x 2.20
T O 10 HJ	7/8"-14 UNF	7/8"-14 UNF	22	27	19.18 x 2.46
T O 12 HJ	1.1/16" -12 UN	1.1/16" -12 UN	27	32	23.47 x 2.95
T O 16 HJ	1.5/16" -12 UN	1.5/16" -12 UN	33	38	29.74 x 2.95
T O 20 HJ	1.5/8" -12 UN	1.5/8" -12 UN	42	48	37.47 x 3.00
T O 24 HJ	1.7/8" -12 UN	1.7/8" -12 UN	48	55	43.69 x 3.00

SW, S1, S2 = With across flats

## Product versions

T O HJ VA Screw-in socket, T shaped, Stainless steel