


| Properties | | | |
|--------------------|--------------------------------------|--|--|
| Connection 1 | UN/UNF external threads | | |
| Sealing form 1 | O-ring seal on screw-in socket | | |
| Connection 2 + 3 | UN/UNF external threads | | |
| Sealing form 2 + 3 | 74° outer cone | | |
| Design | Adjustable direction screw-in socket | | |
| Construction | T shaped | | |
| Material | Stainless steel | | |
| | | | |





Ordering information

Seals of NBR

FPM (Viton) on request

| Item | | | | | | |
|----------------|--------------|--------------|------------|----|--------------|--|
| Identification | G1 | G2 + G3 | AF (mm) | S1 | OR | |
| T O 04 HJ VA | 7/16"-20 UNF | 7/16"-20 UNF | 11 | 14 | 8.92 x 1.83 | |
| T O 06 HJ VA | 9/16"-18 UNF | 9/16"-18 UNF | 14 | 17 | 11.90 x 1.98 | |
| T O 08 HJ VA | 3/4"-16 UNF | 3/4"-16 UNF | 19 | 22 | 16.36 x 2.20 | |

SW, S1, S2 = With across flats

| Product | t versions |
|---------|----------------------------------|
| T O HJ | Screw-in socket, T shaped, Steel |