


# T O HJOF

Screw-in socket, T shaped

## Properties

|                           |                                      |
|---------------------------|--------------------------------------|
| <b>Connection 1</b>       | UN/UNF external threads              |
| <b>Sealing form 1</b>     | O-ring seal on screw-in socket       |
| <b>Connection 2 + 3</b>   | ORFS external threads                |
| <b>Sealing form 2 + 3</b> | flat seal with O-ring                |
| <b>Design</b>             | Adjustable direction screw-in socket |
| <b>Construction</b>       | T shaped                             |
| <b>Material</b>           | Steel                                |
| <b>Surface</b>            | electro galvanised                   |



## Item

| Identification     | G1             | G2 + G3         | AF<br>(mm) | S1 | OR1          | OR2 + OR3    |
|--------------------|----------------|-----------------|------------|----|--------------|--------------|
| <b>T O 04 HJOF</b> | 7/16"-20 UNF   | 9/16"-18 UNF    | 14         | 16 | 8.92 x 1.83  | 7.65 x 1.78  |
| <b>T O 06 HJOF</b> | 9/16"-18 UNF   | 1 1/16" -16 UN  | 19         | 19 | 11.89 x 1.98 | 9.25 x 1.78  |
| <b>T O 08 HJOF</b> | 3/4"-16 UNF    | 1 3/16" -16 UN  | 19         | 24 | 16.36 x 2.21 | 12.42 x 1.78 |
| <b>T O 10 HJOF</b> | 7/8" -14 UNF   | 1" -14 UNS      | 27         | 27 | 19.18 x 2.46 | 15.60 x 1.78 |
| <b>T O 12 HJOF</b> | 1 1/16" -12 UN | 1 3/16" -12 UN  | 30         | 36 | 23.47 x 2.95 | 18.77 x 1.78 |
| <b>T O 16 HJOF</b> | 1 5/16" -12 UN | 1 7/16" -12 UN  | 37         | 41 | 29.74 x 2.95 | 23.52 x 1.78 |
| <b>T O 20 HJOF</b> | 1 5/8" -12 UN  | 1 11/16" -12 UN | 41         | 48 | 37.47 x 3.00 | 29.87 x 1.78 |
| <b>T O 24 HJOF</b> | 1 7/8" -12 UN  | 2" -12 UN       | 48         | 54 | 43.69 x 3.00 | 37.82 x 1.78 |

SW, S1, S2 = With across flats