GMM 100
Pressure gauges with glycerine filling

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	at bottom
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 100-0.6	100	0...0,6	1,0	G 1/2" -14
GMM 100-1	100	0...1	1,0	G 1/2" -14
GMM 100-1.6	100	0...1,6	1,0	G 1/2" -14
GMM 100-2.5	100	0...2,5	1,0	G 1/2" -14
GMM 100-4	100	0...4	1,0	G 1/2" -14
GMM 100-6	100	0...6	1,0	G 1/2" -14
GMM 100-10	100	0...10	1,0	G 1/2" -14
GMM 100-16	100	0...16	1,0	G 1/2" -14
GMM 100-25	100	0...25	1,0	G 1/2" -14
GMM 100-40	100	0...40	1,0	G 1/2" -14
GMM 100-60	100	0...60	1,0	G 1/2" -14
GMM 100-100	100	0...100	1,0	G 1/2" -14
GMM 100-160	100	0...160	1,0	G 1/2" -14
GMM 100-250	100	0...250	1,0	G 1/2" -14
GMM 100-400	100	0...400	1,0	G 1/2" -14
GMM 100-600	100	0...600	1,0	G 1/2" -14
GMM 100-1000	100	0...1000	1,0	G 1/2" -14

Accessories

GMM SCHUTZ	Rubber cap for pressure gauge

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.