

# GMM 100 H

Pressure gauges with glycerine filling

**HANSA FLEX**

## Properties

<b>Design</b>	Pipe spring pressure gauge with glycerine filling
<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	flat seal with pin
<b>Connection</b>	on back, eccentric
<b>Standard</b>	EN 837-1
<b>Damping</b>	due to glycerine filling
<b>Temp. range</b>	medium max. +60 °C Ambient -20 °C to +60 °C



## Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

## Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 100-0.6 H	100	0...0,6	1,0	G 1/2" -14
GMM 100-1 H	100	0...1	1,0	G 1/2" -14
GMM 100-1.6 H	100	0...1,6	1,0	G 1/2" -14
GMM 100-2.5 H	100	0...2,5	1,0	G 1/2" -14
GMM 100-04 H	100	0...4	1,0	G 1/2" -14
GMM 100-06 H	100	0...6	1,0	G 1/2" -14
GMM 100-10 H	100	0...10	1,0	G 1/2" -14
GMM 100-16 H	100	0...16	1,0	G 1/2" -14
GMM 100-25 H	100	0...25	1,0	G 1/2" -14
GMM 100-40 H	100	0...40	1,0	G 1/2" -14
GMM 100-60 H	100	0...60	1,0	G 1/2" -14
GMM 100-100 H	100	0...100	1,0	G 1/2" -14
GMM 100-160 H	100	0...160	1,0	G 1/2" -14
GMM 100-250 H	100	0...250	1,0	G 1/2" -14
GMM 100-400 H	100	0...400	1,0	G 1/2" -14
GMM 100-600 H	100	0...600	1,0	G 1/2" -14