

### Properties

Design	Pipe spring pressure gauge with glycerine filling
Mounting	Front ring with mounting bores
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, eccentric
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



### Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

### Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 100-0.6 HFR	100	0...0,6	1,0	G 1/2" -14
GMM 100-1 HFR	100	0...1	1,0	G 1/2" -14
GMM 100-1.6 HFR	100	0...1,6	1,0	G 1/2" -14
GMM 100-2.5 HFR	100	0...2,5	1,0	G 1/2" -14
GMM 100-4 HFR	100	0...4	1,0	G 1/2" -14
GMM 100-6 HFR	100	0...6	1,0	G 1/2" -14
GMM 100-10 HFR	100	0...10	1,0	G 1/2" -14
GMM 100-16 HFR	100	0...16	1,0	G 1/2" -14
GMM 100-25 HFR	100	0...25	1,0	G 1/2" -14
GMM 100-40 HFR	100	0...40	1,0	G 1/2" -14
GMM 100-60 HFR	100	0...60	1,0	G 1/2" -14
GMM 100-100 HFR	100	0...100	1,0	G 1/2" -14
GMM 100-160 HFR	100	0...160	1,0	G 1/2" -14
GMM 100-250 HFR	100	0...250	1,0	G 1/2" -14
GMM 100-400 HFR	100	0...400	1,0	G 1/2" -14
GMM 100-600 HFR	100	0...600	1,0	G 1/2" -14
GMM 100-1000 HFR	100	0...1000	1,0	G 1/2" -14