

Properties	
Design	Pipe spring pressure gauge with glycerine filling
Mounting	Clamping ring
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, eccentric
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: Up to full scale.

Application range with alternating load: Up to $0.9 \ x$ full scale.

Scale range 00,6 01 01,6 02,5	Quality class 1,0 1,0 1,0	Connection G 1/2" -14 G 1/2" -14 G 1/2" -14
01 01,6	1,0	G 1/2" -14
01,6		
•	1,0	G 1/2" -14
02,5		
	1,0	G 1/2" -14
04	1,0	G 1/2" -14
06	1,0	G 1/2" -14
010	1,0	G 1/2" -14
016	1,0	G 1/2" -14
025	1,0	G 1/2" -14
040	1,0	G 1/2" -14
060	1,0	G 1/2" -14
0100	1,0	G 1/2" -14
0160	1,0	G 1/2" -14
0250	1,0	G 1/2" -14
0400	1,0	G 1/2" -14
0600	1,0	G 1/2" -14
01000	1,0	G 1/2" -14
	04 06 010 016 025 040 060 0100 0160 0250 0400 0600	04 1,0 06 1,0 010 1,0 016 1,0 025 1,0 040 1,0 060 1,0 0100 1,0 0160 1,0 0250 1,0 0400 1,0 0600 1,0 0600 1,0