

Properties

| | |
|----------------|---|
| Design | Pipe spring pressure gauge with glycerine filling |
| Mounting | Clamping ring |
| Connection 1 | BSP external thread, cylindrical |
| Sealing form 1 | flat seal with pin |
| Connection | on back, eccentric |
| Standard | EN 837-1 |
| Damping | due to glycerine filling |
| Temp. range | medium max. +60 °C Ambient -20 °C to +60 °C |



Note

Application range at idle load: Up to full scale.

Application range with alternating load: Up to 0.9 x full scale.

Item

| Identification | Nominal size Ø | Scale range | Quality class | Connection |
|------------------|----------------|-------------|---------------|------------|
| GMM 100-0.6 HKR | 100 | 0...0,6 | 1,0 | G 1/2" -14 |
| GMM 100-1 HKR | 100 | 0...1 | 1,0 | G 1/2" -14 |
| GMM 100-1.6 HKR | 100 | 0...1,6 | 1,0 | G 1/2" -14 |
| GMM 100-2.5 HKR | 100 | 0...2,5 | 1,0 | G 1/2" -14 |
| GMM 100-4 HKR | 100 | 0...4 | 1,0 | G 1/2" -14 |
| GMM 100-6 HKR | 100 | 0...6 | 1,0 | G 1/2" -14 |
| GMM 100-10 HKR | 100 | 0...10 | 1,0 | G 1/2" -14 |
| GMM 100-16 HKR | 100 | 0...16 | 1,0 | G 1/2" -14 |
| GMM 100-25 HKR | 100 | 0...25 | 1,0 | G 1/2" -14 |
| GMM 100-40 HKR | 100 | 0...40 | 1,0 | G 1/2" -14 |
| GMM 100-60 HKR | 100 | 0...60 | 1,0 | G 1/2" -14 |
| GMM 100-100 HKR | 100 | 0...100 | 1,0 | G 1/2" -14 |
| GMM 100-160 HKR | 100 | 0...160 | 1,0 | G 1/2" -14 |
| GMM 100-250 HKR | 100 | 0...250 | 1,0 | G 1/2" -14 |
| GMM 100-400 HKR | 100 | 0...400 | 1,0 | G 1/2" -14 |
| GMM 100-600 HKR | 100 | 0...600 | 1,0 | G 1/2" -14 |
| GMM 100-1000 HKR | 100 | 0...1000 | 1,0 | G 1/2" -14 |