

Properties			
Design	Pipe spring pressure gauge with glycerine filling		
Connection 1	BSP external thread, cylindrical		
Sealing form 1	flat seal with pin		
Connection	at bottom		
Standard	EN 837-1		
Damping	due to glycerine filling		
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C		



## Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

Item				
Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 160-0.6	160	00,6	1,0	G 1/2" -14
GMM 160-1	160	01	1,0	G 1/2" -14
GMM 160-1.6	160	01,6	1,0	G 1/2" -14
GMM 160-2.5	160	02,5	1,0	G 1/2" -14
GMM 160-4	160	04	1,0	G 1/2" -14
GMM 160-6	160	06	1,0	G 1/2" -14
GMM 160-10	160	010	1,0	G 1/2" -14
GMM 160-16	160	016	1,0	G 1/2" -14
GMM 160-25	160	025	1,0	G 1/2" -14
GMM 160-40	160	040	1,0	G 1/2" -14
GMM 160-60	160	060	1,0	G 1/2" -14
GMM 160-100	160	0100	1,0	G 1/2" -14
GMM 160-160	160	0160	1,0	G 1/2" -14
GMM 160-250	160	0250	1,0	G 1/2" -14
GMM 160-400	160	0400	1,0	G 1/2" -14
GMM 160-600	160	0600	1,0	G 1/2" -14
GMM 160-1000	160	01000	1,0	G 1/2" -14