GMM 160 H

Pressure gauges with glycerine filling

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, eccentric
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 160-1 H	160	0...1	1,0	G 1/2" -14
GMM 160-1.6 H	160	0...1,6	1,0	G 1/2" -14
GMM 160-2.5 H	160	0...2,5	1,0	G 1/2" -14
GMM 160-4 H	160	0...4	1,0	G 1/2" -14
GMM 160-6 H	160	0...6	1,0	G 1/2" -14
GMM 160-10 H	160	0...10	1,0	G 1/2" -14
GMM 160-16 H	160	0...16	1,0	G 1/2" -14
GMM 160-25 H	160	0...25	1,0	G 1/2" -14
GMM 160-40 H	160	0...40	1,0	G 1/2" -14
GMM 160-60 H	160	0...60	1,0	G 1/2" -14
GMM 160-100 H	160	0...100	1,0	G 1/2" -14
GMM 160-160 H	160	0...160	1,0	G 1/2" -14
GMM 160-250 H	160	0...250	1,0	G 1/2" -14
GMM 160-400 H	160	0...400	1,0	G 1/2" -14
GMM 160-600 H	160	0...600	1,0	G 1/2" -14
GMM 160-1000 H	160	0...1000	1,0	G 1/2" -14

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.