

GMM 50

Pressure gauges with glycerine filling

HANSA FLEX

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	at bottom
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 50-1	50	0...1	2,5	G 1/4" -19
GMM 50-1.6	50	0...1,6	2,5	G 1/4" -19
GMM 50-2.5	50	0...2,5	2,5	G 1/4" -19
GMM 50-4	50	0...4	2,5	G 1/4" -19
GMM 50-6	50	0...6	2,5	G 1/4" -19
GMM 50-10	50	0...10	2,5	G 1/4" -19
GMM 50-16	50	0...16	2,5	G 1/4" -19
GMM 50-25	50	0...25	2,5	G 1/4" -19
GMM 50-40	50	0...40	2,5	G 1/4" -19
GMM 50-60	50	0...60	2,5	G 1/4" -19
GMM 50-100	50	0...100	2,5	G 1/4" -19
GMM 50-160	50	0...160	2,5	G 1/4" -19
GMM 50-250	50	0...250	2,5	G 1/4" -19
GMM 50-400	50	0...400	2,5	G 1/4" -19