

GMM 63

Pressure gauges with glycerine filling

HANSA FLEX

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	at bottom
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 63-1	63	0...1	1,6	G 1/4" -19
GMM 63-1.5	63	0...1,5	1,6	G 1/4" -19
GMM 63-2.5	63	0...2,5	1,6	G 1/4" -19
GMM 63-4	63	0...4	1,6	G 1/4" -19
GMM 63-06	63	0...6	1,6	G 1/4" -19
GMM 63-10	63	0...10	1,6	G 1/4" -19
GMM 63-16	63	0...16	1,6	G 1/4" -19
GMM 63-25	63	0...25	1,6	G 1/4" -19
GMM 63-40	63	0...40	1,6	G 1/4" -19
GMM 63-60	63	0...60	1,6	G 1/4" -19
GMM 63-100	63	0...100	1,6	G 1/4" -19
GMM 63-160	63	0...160	1,6	G 1/4" -19
GMM 63-250	63	0...250	1,6	G 1/4" -19
GMM 63-400	63	0...400	1,6	G 1/4" -19
GMM 63-600	63	0...600	1,6	G 1/4" -19
GMM 63-1000	63	0...1000	1,6	G 1/4" -19

Accessories

GMM SCHUTZ	Rubber cap for pressure gauge
-------------------	-------------------------------