GMM 63 H

Pressure gauges with glycerine filling

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, centric
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 63-1 H	63	0...1	1,6	G 1/4" -19
GMM 63-1.6 H	63	0...1,6	1,6	G 1/4" -19
GMM 63-2.5 H	63	0...2,5	1,6	G 1/4" -19
GMM 63-04 H	63	0...4	1,6	G 1/4" -19
GMM 63-06 H	63	0...6	1,6	G 1/4" -19
GMM 63-10 H	63	0...10	1,6	G 1/4" -19
GMM 63-16 H	63	0...16	1,6	G 1/4" -19
GMM 63-25 H	63	0...25	1,6	G 1/4" -19
GMM 63-40 H	63	0...40	1,6	G 1/4" -19
GMM 63-60 H	63	0...60	1,6	G 1/4" -19
GMM 63-100 H	63	0...100	1,6	G 1/4" -19
GMM 63-160 H	63	0...160	1,6	G 1/4" -19
GMM 63-250 H	63	0...250	1,6	G 1/4" -19
GMM 63-400 H	63	0...400	1,6	G 1/4" -19
GMM 63-600 H	63	0...600	1,6	G 1/4" -19

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.