GMM 80

Pressure gauges with glycerine filling

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	at bottom
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GMM 80-1	80	0...1	1,6	G 1/2" -14
GMM 80-1.6	80	0...1,6	1,6	G 1/2" -14
GMM 80-2.5	80	0...2,5	1,6	G 1/2" -14
GMM 80-4	80	0...4	1,6	G 1/2" -14
GMM 80-6	80	0...6	1,6	G 1/2" -14
GMM 80-10	80	0...10	1,6	G 1/2" -14
GMM 80-16	80	0...16	1,6	G 1/2" -14
GMM 80-25	80	0...25	1,6	G 1/2" -14
GMM 80-40	80	0...40	1,6	G 1/2" -14
GMM 80-60	80	0...60	1,6	G 1/2" -14
GMM 80-100	80	0...100	1,6	G 1/2" -14
GMM 80-160	80	0...160	1,6	G 1/2" -14
GMM 80-250	80	0...250	1,6	G 1/2" -14
GMM 80-400	80	0...400	1,6	G 1/2" -14
GMM 80-600	80	0...600	1,6	G 1/2" -14

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.