

GVM 100

Vacuum pressure gauges with glycerine filling

HANSA FLEX

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	at bottom
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GVM 100 -0.6+0	100	-0,6...0	1,0	G 1/2" -14
GVM 100 -1+0	100	-1...0	1,0	G 1/2" -14
GVM 100 -1+0.6	100	-1...+0,6	1,0	G 1/2" -14
GVM 100 -1+1.5	100	-1...+1,5	1,0	G 1/2" -14
GVM 100 -1+3	100	-1...+3	1,0	G 1/2" -14
GVM 100 -1+5	100	-1...+5	1,0	G 1/2" -14
GVM 100 -1+9	100	-1...+9	1,0	G 1/2" -14
GVM 100 -1+15	100	-1...+15	1,0	G 1/2" -14

Accessories

GMM SCHUTZ	Rubber cap for pressure gauge
-------------------	-------------------------------