GVM 100 H

Vacuum pressure gauges with glycerine filling

Properties

Design	Pipe spring pressure gauge with glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, eccentric
Standard	EN 837-1
Damping	due to glycerine filling
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GVM 100 -0.6+0 H	100	-0,6...0	1,0	G 1/2" -14
GVM 100 -1+0 H	100	-1...0	1,0	G 1/2" -14
GVM 100 -1+0.6 H	100	-1...+0,6	1,0	G 1/2" -14
GVM 100 -1+1.5 H	100	-1...+1,5	1,0	G 1/2" -14
GVM 100 -1+3 H	100	-1...+3	1,0	G 1/2" -14
GVM 100 -1+5 H	100	-1...+5	1,0	G 1/2" -14
GVM 100 -1+9 H	100	-1...+9	1,0	G 1/2" -14
GVM 100 -1+15 H	100	-1...+15	1,0	G 1/2" -14

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.