

Properties			
Design	Pipe spring pressure gauge with glycerine filling		
Mounting	Clamping ring		
Connection 1	BSP external thread, cylindrical		
Sealing form 1	flat seal with pin		
Connection	on back, eccentric		
Standard	EN 837-1		
Damping	due to glycerine filling		
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C		



Note

Application range at idle load: Up to full scale.

Application range with alternating load: Up to 0.9 x full scale.

Item					
Identification	Nominal size Ø	Scale range	Quality class	Connection	
GVM 100 -0.6+0 HKR	100	-0,60	1,0	G 1/2" -14	
GVM 100 -1+0 HKR	100	-10	1,0	G 1/2" -14	
GVM 100 -1+0.6 HKR	100	-1+0,6	1,0	G 1/2" -14	
GVM 100 -1+1.5 HKR	100	-1+1,5	1,0	G 1/2" -14	
GVM 100 -1+3 HKR	100	-1+3	1,0	G 1/2" -14	
GVM 100 -1+5 HKR	100	-1+5	1,0	G 1/2" -14	
GVM 100 -1+9 HKR	100	-1+9	1,0	G 1/2" -14	
GVM 100 -1+15 HKR	100	-1+15	1,0	G 1/2" -14	