

# GVM 160

Vacuum pressure gauges with glycerine filling

## Properties

<b>Design</b>	Pipe spring pressure gauge with glycerine filling
<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	flat seal with pin
<b>Connection</b>	at bottom
<b>Standard</b>	EN 837-1
<b>Damping</b>	due to glycerine filling
<b>Temp. range</b>	medium max. +60 °C Ambient -20 °C to +60 °C



## Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

## Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
<b>GVM 160 -1+0</b>	160	-1...0	1,0	G 1/2" -14
<b>GVM 160 -1+0.6</b>	160	-1...+0,6	1,0	G 1/2" -14
<b>GVM 160 -1+1.5</b>	160	-1...+1,5	1,0	G 1/2" -14
<b>GVM 160 -1+3</b>	160	-1...+3	1,0	G 1/2" -14
<b>GVM 160 -1+5</b>	160	-1...+5	1,0	G 1/2" -14
<b>GVM 160 -1+9</b>	160	-1...+9	1,0	G 1/2" -14
<b>GVM 160 -1+15</b>	160	-1...+15	1,0	G 1/2" -14