

# GVM 160

Vacuum pressure gauges with glycerine filling

**HANSA FLEX**

## Properties

<b>Design</b>	Pipe spring pressure gauge with glycerine filling
<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	flat seal with pin
<b>Connection</b>	at bottom
<b>Standard</b>	EN 837-1
<b>Damping</b>	due to glycerine filling
<b>Temp. range</b>	medium max. +60 °C Ambient -20 °C to +60 °C



## Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

## Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
GVM 160 -1+0	160	-1...0	1,0	G 1/2" -14
GVM 160 -1+0.6	160	-1...+0,6	1,0	G 1/2" -14
GVM 160 -1+1.5	160	-1...+1,5	1,0	G 1/2" -14
GVM 160 -1+3	160	-1...+3	1,0	G 1/2" -14
GVM 160 -1+5	160	-1...+5	1,0	G 1/2" -14
GVM 160 -1+9	160	-1...+9	1,0	G 1/2" -14
GVM 160 -1+15	160	-1...+15	1,0	G 1/2" -14