# GVM 80 H

Vacuum pressure gauges with glycerine filling

## Properties

| | |
|---|---|
| **Design** | Pipe spring pressure gauge with glycerine filling |
| **Connection 1** | BSP external thread, cylindrical |
| **Sealing form 1** | flat seal with pin |
| **Connection** | on back, centric |
| **Standard** | EN 837-1 |
| **Damping** | due to glycerine filling |
| **Temp. range** | medium max. +60 °C<br>Ambient -20 °C to +60 °C |




## Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

## Item

| Identification | Nominal size Ø | Scale range | Quality class | Connection |
|---|---|---|---|---|
| **GVM 80 -0.6+0 H** | 80 | -0,6...0 | 1,6 | G 1/4" -19 |
| **GVM 80 -1+0 H** | 80 | -1...0 | 1,6 | G 1/4" -19 |
| **GVM 80 -1+0.6 H** | 80 | -1...+0,6 | 1,6 | G 1/4" -19 |
| **GVM 80 -1+1.5 H** | 80 | -1...+1,5 | 1,6 | G 1/4" -19 |
| **GVM 80 -1+3 H** | 80 | -1...+3 | 1,6 | G 1/4" -19 |
| **GVM 80 -1+5 H** | 80 | -1...+5 | 1,6 | G 1/4" -19 |
| **GVM 80 -1+9 H** | 80 | -1...+9 | 1,6 | G 1/4" -19 |
| **GVM 80 -1+15 H** | 80 | -1...+15 | 1,6 | G 1/4" -19 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*