

# HFM SKE

## Measuring hose line

### Properties

<b>Application</b>	Measuring equipment
<b>Design</b>	Hose line DN 2 with M 16 x 2 measuring connections
<b>Inner layer</b>	Polyamide
<b>Insert</b>	one aramide braided insert
<b>Outer layer</b>	Polyurethane
<b>Scope of supply</b>	with dust protection
<b>Temp. min.</b>	-20 °C
<b>Temp. max.</b>	100 °C
<b>Media</b>	Liquids based on mineral oil and glycol



### Item

Identification	External Ø (mm)	Internal Ø (mm)	Max. working pressure (bar)	Min. bending radius (mm)	Length (mm)
HFM SKE 200	5,5	2	630	35	200
HFM SKE 300	5,5	2	630	35	300
HFM SKE 400	5,5	2	630	35	400
HFM SKE 630	5,5	2	630	35	630
HFM SKE 800	5,5	2	630	35	800
HFM SKE 1000	5,5	2	630	35	1000
HFM SKE 1500	5,5	2	630	35	1500
HFM SKE 2000	5,5	2	630	35	2000
HFM SKE 2500	5,5	2	630	35	2500
HFM SKE 3200	5,5	2	630	35	3200
HFM SKE 4000	5,5	2	630	35	4000

### Product versions

HFM SKE VA