HFM SKE VA
Measuring hose line

Properties

Application	Measuring equipment
Design	Hose line DN 2 with M 16 x 2 measuring connections
Inner layer	Polyamide
Insert	one aramide braided insert
Outer layer	Polyurethane
Scope of supply	with dust protection
Temp. min.	-20 °C
Temp. max.	100 °C
Media	Liquids based on mineral oil and glycol



Note
The connections are stainless steel.

Item

Identification	External Ø (mm)	Internal Ø (mm)	Max. working pressure (bar)	Min. bending radius (mm)	Length (mm)
HFM SKE 200 VA	5,5	2	630	35	200
HFM SKE 300 VA	5,5	2	630	35	300
HFM SKE 400 VA	5,5	2	630	35	400
HFM SKE 630 VA	5,5	2	630	35	630
HFM SKE 800 VA	5,5	2	630	35	800
HFM SKE 1000 VA	5,5	2	630	35	1000
HFM SKE 1500 VA	5,5	2	630	35	1500
HFM SKE 2000 VA	5,5	2	630	35	2000
HFM SKE 2500 VA	5,5	2	630	35	2500
HFM SKE 3200 VA	5,5	2	630	35	3200
HFM SKE 4000 VA	5,5	2	630	35	4000

Product versions
HFM SKE

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.