HFM T AJ HJ Measuring connection, M16 x 2 series

HANSA/FLEX

Properties

i ioperties					
Connection 1	Measuring connection M 16 x 2				
Connection 2	UN/UNF nut threads				
Sealing form 2	74° inner cone				
Connection 3	UN/UNF external threads				
Sealing form 3	74° outer cone				
Design	Adapter for test connection				
Construction	T shaped				
Scope of supply	with cap				
Temp. min.	-20 °C				
Temp. max.	100 °C				
Material	Steel				
Surface	electro galvanised				





Item

Identification	G1	G2 + G3	Max. working pressure	AF	S1
			(bar)	(mm)	
HFM T AJ 05 HJ	M 16 x 2	1/2"-20 UNF	420	36	17
HFM T AJ 06 HJ	M 16 x 2	9/16"-18 UNF	350	36	19
HFM T AJ 08 HJ	M 16 x 2	3/4"-16 UNF	350	36	22
HFM T AJ 10 HJ	M 16 x 2	7/8"-14 UNF	350	36	27
HFM T AJ 12 HJ	M 16 x 2	1.1/16" -12 UN	350	41	32
HFM T AJ 16 HJ	M 16 x 2	1.5/16" -12 UN	250	46	38

Spare parts

HFM VK Cap