

# HFM T HL S / HFM T HS S

Measuring connection, plug-in series

**HANSA FLEX**

## Properties

<b>Connection 1 + 2</b>	metric cylindrical outer thread
<b>Sealing form 1 + 2</b>	24° inner cone
<b>Connection 3</b>	Plug connection for measuring technology
<b>Construction</b>	T shaped
<b>Standard</b>	DIN 2353 ISO 8434-1
<b>Scope of supply</b>	with locking connector and retaining pin
<b>Temp. min.</b>	-20 °C
<b>Temp. max.</b>	100 °C
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Note

Information about fitting, installation, pressure loads and permissible operating temperatures can be found in the technical information for pipe fittings.

## Item

Identification	Series	External pipe Ø (mm)	G1 + G2	Max. working pressure (bar)
HFM T HL 04 S	L	6	M 12 x 1.5	315
HFM T HL 06 S	L	8	M 14 x 1.5	315
HFM T HL 08 S	L	10	M 16 x 1.5	315
HFM T HL 10 S	L	12	M 18 x 1.5	315
HFM T HL 13 S	L	15	M 22 x 1.5	315
HFM T HL 16 S	L	18	M 26 x 1.5	315
HFM T HL 20 S	L	22	M 30 x 2	160
HFM T HL 25 S	L	28	M 36 x 2	160
HFM T HL 32 S	L	35	M 45 x 2	160
HFM T HL 40 S	L	42	M 52 x 2	160
HFM T HS 03 S	S	6	M 14 x 1.5	400
HFM T HS 04 S	S	8	M 16 x 1.5	400
HFM T HS 06 S	S	10	M 18 x 1.5	400
HFM T HS 08 S	S	12	M 20 x 1.5	400
HFM T HS 10 S	S	14	M 22 x 1.5	400
HFM T HS 13 S	S	16	M 24 x 1.5	400
HFM T HS 16 S	S	20	M 30 x 2	400
HFM T HS 20 S	S	25	M 36 x 2	400
HFM T HS 25 S	S	30	M 42 x 2	400
HFM T HS 32 S	S	38	M 52 x 2	315

## Product versions

XHFM T HL S / XHFM T HS S Measuring connection, plug-in series, Socket (without union nut and cutting ring)

## Spare parts

HFM ST Locking connector for plug-in coupling DN 2