

# RMM 160

Pressure gauges without glycerine filling

**HANSA FLEX**

## Properties

<b>Design</b>	Pipe spring pressure gauge without glycerine filling
<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	flat seal with pin
<b>Connection</b>	at bottom
<b>Standard</b>	EN 837-1
<b>Temp. range</b>	medium max. +60 °C Ambient -20 °C to +60 °C



## Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

## Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 160-0.6	160	0...0,6	1,6	G 1/2" -14
RMM 160-1	160	0...1	1,6	G 1/2" -14
RMM 160-1.6	160	0...1,6	1,6	G 1/2" -14
RMM 160-2.5	160	0...2,5	1,6	G 1/2" -14
RMM 160-4	160	0...4	1,6	G 1/2" -14
RMM 160-6	160	0...6	1,6	G 1/2" -14
RMM 160-10	160	0...10	1,6	G 1/2" -14
RMM 160-16	160	0...16	1,6	G 1/2" -14
RMM 160-25	160	0...25	1,6	G 1/2" -14
RMM 160-40	160	0...40	1,6	G 1/2" -14