RMM 160
Pressure gauges without glycerine filling

Properties

Design	Pipe spring pressure gauge without glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	at bottom
Standard	EN 837-1
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 160-0.6	160	0...0,6	1,6	G 1/2" -14
RMM 160-1	160	0...1	1,6	G 1/2" -14
RMM 160-1.6	160	0...1,6	1,6	G 1/2" -14
RMM 160-2.5	160	0...2,5	1,6	G 1/2" -14
RMM 160-4	160	0...4	1,6	G 1/2" -14
RMM 160-6	160	0...6	1,6	G 1/2" -14
RMM 160-10	160	0...10	1,6	G 1/2" -14
RMM 160-16	160	0...16	1,6	G 1/2" -14
RMM 160-25	160	0...25	1,6	G 1/2" -14
RMM 160-40	160	0...40	1,6	G 1/2" -14

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.