

# RMM 40 H

Pressure gauges without glycerine filling

**HANSA FLEX**

## Properties

<b>Design</b>	Pipe spring pressure gauge without glycerine filling
<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	flat seal with pin
<b>Connection</b>	on back, centric
<b>Standard</b>	EN 837-1
<b>Temp. range</b>	medium max. +60 °C Ambient -20 °C to +60 °C



## Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

## Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 40-1-1/8 H	40	0...1	2,5	G 1/8" -28
RMM 40-1.6-1/8 H	40	0...1,6	2,5	G 1/8" -28
RMM 40-2.5-1/8 H	40	0...2,5	2,5	G 1/8" -28
RMM 40-4-1/8 H	40	0...4	2,5	G 1/8" -28
RMM 40-6-1/8 H	40	0...6	2,5	G 1/8" -28
RMM 40-10-1/8 H	40	0...10	2,5	G 1/8" -28
RMM 40-16-1/8 H	40	0...16	2,5	G 1/8" -28
RMM 40-25-1/8 H	40	0...25	2,5	G 1/8" -28
RMM 40-40-1/8 H	40	0...40	2,5	G 1/8" -28
RMM 40-60-1/8 H	40	0...60	2,5	G 1/8" -28
RMM 40-100-1/8 H	40	0...100	2,5	G 1/8" -28
RMM 40-160-1/8 H	40	0...160	2,5	G 1/8" -28
RMM 40-250-1/8 H	40	0...250	2,5	G 1/8" -28
RMM 40-315-1/8 H	40	0...315	2,5	G 1/8" -28
RMM 40-400-1/8 H	40	0...400	2,5	G 1/8" -28
RMM 40-1 H	40	0...1	2,5	G 1/4" -19
RMM 40-1.6 H	40	0...1,6	2,5	G 1/4" -19
RMM 40-2.5 H	40	0...2,5	2,5	G 1/4" -19
RMM 40-4 H	40	0...4	2,5	G 1/4" -19
RMM 40-6 H	40	0...6	2,5	G 1/4" -19
RMM 40-10 H	40	0...10	2,5	G 1/4" -19
RMM 40-16 H	40	0...16	2,5	G 1/4" -19
RMM 40-25 H	40	0...25	2,5	G 1/4" -19
RMM 40-40 H	40	0...40	2,5	G 1/4" -19
RMM 40-60 H	40	0...60	2,5	G 1/4" -19
RMM 40-100 H	40	0...100	2,5	G 1/4" -19
RMM 40-160 H	40	0...160	2,5	G 1/4" -19
RMM 40-250 H	40	0...250	2,5	G 1/4" -19
RMM 40-315 H	40	0...315	2,5	G 1/4" -19
RMM 40-400 H	40	0...400	2,5	G 1/4" -19