

RMM 40 HKR

Pressure gauges without glycerine filling

HANSA FLEX

Properties

| | |
|-----------------------|--|
| Design | Pipe spring pressure gauge without glycerine filling |
| Mounting | Clamping ring |
| Connection 1 | BSP external thread, cylindrical |
| Sealing form 1 | flat seal with pin |
| Connection | on back, centric |
| Standard | EN 837-1 |
| Temp. range | medium max. +60 °C Ambient -20 °C to +60 °C |



Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

Item

| Identification | Nominal size Ø | Scale range | Quality class | Connection |
|----------------|----------------|-------------|---------------|------------|
| RMM 40-1 HKR | 40 | 0...1 | 2,5 | G 1/4" -19 |
| RMM 40-1.6 HKR | 40 | 0...1,6 | 2,5 | G 1/4" -19 |
| RMM 40-2.5 HKR | 40 | 0...2,5 | 2,5 | G 1/4" -19 |
| RMM 40-4 HKR | 40 | 0...4 | 2,5 | G 1/4" -19 |
| RMM 40-6 HKR | 40 | 0...6 | 2,5 | G 1/4" -19 |
| RMM 40-10 HKR | 40 | 0...10 | 2,5 | G 1/4" -19 |
| RMM 40-16 HKR | 40 | 0...16 | 2,5 | G 1/4" -19 |
| RMM 40-25 HKR | 40 | 0...25 | 2,5 | G 1/4" -19 |
| RMM 40-40 HKR | 40 | 0...40 | 2,5 | G 1/4" -19 |
| RMM 40-60 HKR | 40 | 0...60 | 2,5 | G 1/4" -19 |
| RMM 40-100 HKR | 40 | 0...100 | 2,5 | G 1/4" -19 |
| RMM 40-160 HKR | 40 | 0...160 | 2,5 | G 1/4" -19 |
| RMM 40-250 HKR | 40 | 0...250 | 2,5 | G 1/4" -19 |
| RMM 40-315 HKR | 40 | 0...315 | 2,5 | G 1/4" -19 |
| RMM 40-400 HKR | 40 | 0...400 | 2,5 | G 1/4" -19 |