

# RMM 50 H

Pressure gauges without glycerine filling

**HANSA FLEX**

## Properties

<b>Design</b>	Pipe spring pressure gauge without glycerine filling
<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	flat seal with pin
<b>Connection</b>	on back, centric
<b>Standard</b>	EN 837-1
<b>Temp. range</b>	medium max. +60 °C Ambient -20 °C to +60 °C



## Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

## Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 50-0.6 H	50	0...0,6	2,5	G 1/4" -19
RMM 50-1 H	50	0...1	2,5	G 1/4" -19
RMM 50-1.6 H	50	0...1,6	2,5	G 1/4" -19
RMM 50-2.5 H	50	0...2,5	2,5	G 1/4" -19
RMM 50-4 H	50	0...4	2,5	G 1/4" -19
RMM 50-6 H	50	0...6	2,5	G 1/4" -19
RMM 50-10 H	50	0...10	2,5	G 1/4" -19
RMM 50-16 H	50	0...16	2,5	G 1/4" -19
RMM 50-25 H	50	0...25	2,5	G 1/4" -19
RMM 50-40 H	50	0...40	2,5	G 1/4" -19
RMM 50-60 H	50	0...60	2,5	G 1/4" -19
RMM 50-100 H	50	0...100	2,5	G 1/4" -19
RMM 50-160 H	50	0...160	2,5	G 1/4" -19
RMM 50-250 H	50	0...250	2,5	G 1/4" -19
RMM 50-315 H	50	0...315	2,5	G 1/4" -19
RMM 50-400 H	50	0...400	2,5	G 1/4" -19