

RMM 50 HKR

Pressure gauges without glycerine filling

Properties

Design	Pipe spring pressure gauge without glycerine filling
Mounting	Clamping ring
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, centric
Standard	EN 837-1
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 50-0.6 HKR	50	0...0,6	2,5	G 1/4" -19
RMM 50-1 HKR	50	0...1	2,5	G 1/4" -19
RMM 50-2.5 HKR	50	0...2,5	2,5	G 1/4" -19
RMM 50-4 HKR	50	0...4	2,5	G 1/4" -19
RMM 50-6 HKR	50	0...6	2,5	G 1/4" -19
RMM 50-10 HKR	50	0...10	2,5	G 1/4" -19
RMM 50-16 HKR	50	0...16	2,5	G 1/4" -19
RMM 50-25 HKR	50	0...25	2,5	G 1/4" -19
RMM 50-40 HKR	50	0...40	2,5	G 1/4" -19
RMM 50-60 HKR	50	0...60	2,5	G 1/4" -19
RMM 50-100 HKR	50	0...100	2,5	G 1/4" -19
RMM 50-160 HKR	50	0...160	2,5	G 1/4" -19
RMM 50-250 HKR	50	0...250	2,5	G 1/4" -19
RMM 50-315 HKR	50	0...315	2,5	G 1/4" -19
RMM 50-400 HKR	50	0...400	2,5	G 1/4" -19