RMM 63
Pressure gauges without glycerine filling

Properties

Design	Pipe spring pressure gauge without glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	at bottom
Standard	EN 837-1
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 63-0.6	63	0...0,6	2,5	G 1/4" -19
RMM 63-1	63	0...1	2,5	G 1/4" -19
RMM 63-1.6	63	0...1,6	2,5	G 1/4" -19
RMM 63-2.5	63	0...2,5	2,5	G 1/4" -19
RMM 63-4	63	0...4	2,5	G 1/4" -19
RMM 63-06	63	0...6	2,5	G 1/4" -19
RMM 63-10	63	0...10	2,5	G 1/4" -19
RMM 63-16	63	0...16	2,5	G 1/4" -19
RMM 63-25	63	0...25	2,5	G 1/4" -19
RMM 63-40	63	0...40	2,5	G 1/4" -19
RMM 63-60	63	0...60	2,5	G 1/4" -19
RMM 63-100	63	0...100	2,5	G 1/4" -19
RMM 63-160	63	0...160	2,5	G 1/4" -19
RMM 63-250	63	0...250	2,5	G 1/4" -19
RMM 63-315	63	0...315	2,5	G 1/4" -19
RMM 63-400	63	0...400	2,5	G 1/4" -19

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.