RMM 63 H

Pressure gauges without glycerine filling

Properties

Design	Pipe spring pressure gauge without glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, centric
Standard	EN 837-1
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 63-0.6 H	63	0...0,6	2,5	G 1/4" -19
RMM 63-1 H	63	0...1	2,5	G 1/4" -19
RMM 63-1.6 H	63	0...1,6	2,5	G 1/4" -19
RMM 63-2.5 H	63	0...2,5	2,5	G 1/4" -19
RMM 63-4 H	63	0...4	2,5	G 1/4" -19
RMM 63-6 H	63	0...6	2,5	G 1/4" -19
RMM 63-10 H	63	0...10	2,5	G 1/4" -19
RMM 63-16 H	63	0...16	2,5	G 1/4" -19
RMM 63-25 H	63	0...25	2,5	G 1/4" -19
RMM 63-40 H	63	0...40	2,5	G 1/4" -19
RMM 63-60 H	63	0...60	2,5	G 1/4" -19
RMM 63-100 H	63	0...100	2,5	G 1/4" -19
RMM 63-160 H	63	0...160	2,5	G 1/4" -19
RMM 63-250 H	63	0...250	2,5	G 1/4" -19
RMM 63-315 H	63	0...315	2,5	G 1/4" -19
RMM 63-400 H	63	0...400	2,5	G 1/4" -19

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.