RMM 63 HKR

Pressure gauges without glycerine filling

Properties

Design	Pipe spring pressure gauge without glycerine filling
Mounting	Clamping ring
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, centric
Standard	EN 837-1
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 63-0.6 HKR	63	0...0,6	2,5	G 1/4" -19
RMM 63-1 HKR	63	0...1	2,5	G 1/4" -19
RMM 63-1.6 HKR	63	0...1,6	2,5	G 1/4" -19
RMM 63-2.5 HKR	63	0...2,5	2,5	G 1/4" -19
RMM 63-4 HKR	63	0...4	2,5	G 1/4" -19
RMM 63-6 HKR	63	0...6	2,5	G 1/4" -19
RMM 63-10 HKR	63	0...10	2,5	G 1/4" -19
RMM 63-16 HKR	63	0...16	2,5	G 1/4" -19
RMM 63-25 HKR	63	0...25	2,5	G 1/4" -19
RMM 63-40 HKR	63	0...40	2,5	G 1/4" -19
RMM 63-60 HKR	63	0...60	2,5	G 1/4" -19
RMM 63-100 HKR	63	0...100	2,5	G 1/4" -19
RMM 63-160 HKR	63	0...160	2,5	G 1/4" -19
RMM 63-250 HKR	63	0...250	2,5	G 1/4" -19
RMM 63-315 HKR	63	0...315	2,5	G 1/4" -19
RMM 63-400 HKR	63	0...400	2,5	G 1/4" -19

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.