RMM 80 H 1/4

Pressure gauges without glycerine filling

Properties

Design	Pipe spring pressure gauge without glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal with pin
Connection	on back, centric
Standard	EN 837-1
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RMM 80-0.6 H 1/4	80	0...0,6	1,6	G 1/4" -19
RMM 80-1 H 1/4	80	0...1	1,6	G 1/4" -19
RMM 80-1.6 H 1/4	80	0...1,6	1,6	G 1/4" -19
RMM 80-2.5 H 1/4	80	0...2,5	1,6	G 1/4" -19
RMM 80-4 H 1/4	80	0...4	1,6	G 1/4" -19
RMM 80-6 H 1/4	80	0...6	1,6	G 1/4" -19
RMM 80-10 H 1/4	80	0...10	1,6	G 1/4" -19
RMM 80-16 H 1/4	80	0...16	1,6	G 1/4" -19
RMM 80-25 H 1/4	80	0...25	1,6	G 1/4" -19
RMM 80-40 H 1/4	80	0...40	1,6	G 1/4" -19
RMM 80-60 H 1/4	80	0...60	1,6	G 1/4" -19
RMM 80-160 H 1/4	80	0...160	1,6	G 1/4" -19
RMM 80-250 H 1/4	80	0...250	1,6	G 1/4" -19
RMM 80-315 H 1/4	80	0...315	1,6	G 1/4" -19
RMM 80-400 H 1/4	80	0...400	1,6	G 1/4" -19

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.