RVM 40 H

Vacuum pressure gauges without glycerine filling

Properties

Design	Pipe spring pressure gauge without glycerine filling
Connection 1	BSP external thread, cylindrical
Sealing form 1	flat seal without pin
Connection	on back, centric
Standard	EN 837-1
Temp. range	medium max. +60 °C Ambient -20 °C to +60 °C



Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

Item

Identification	Nominal size Ø	Scale range	Quality class	Connection
RVM 40 -1 +0H 1/8	40	-1...0	2,5	G 1/8" -28
RVM 40 -1 +0.6 H 1/8	40	-1...+0,6	2,5	G 1/8" -28
RVM 40 -1 +1.5 H 1/8	40	-1...+1,5	2,5	G 1/8" -28
RVM 40 -1 +3 H 1/8	40	-1...+3	2,5	G 1/8" -28
RVM 40 -1 +5 H 1/8	40	-1...+5	2,5	G 1/8" -28
RVM 40 -1 +9 H 1/8	40	-1...+9	2,5	G 1/8" -28
RVM 40 -1 +15 H 1/8	40	-1...+15	2,5	G 1/8" -28
RVM 40 -1 +0H	40	-1...0	2,5	G 1/4" -19
RVM 40 -1 +0.6 H	40	-1...+0,6	2,5	G 1/4" -19
RVM 40 -1 +1.5 H	40	-1...+1,5	2,5	G 1/4" -19
RVM 40 -1 +3 H	40	-1...+3	2,5	G 1/4" -19
RVM 40 -1 +5 H	40	-1...+5	2,5	G 1/4" -19
RVM 40 -1 +9 H	40	-1...+9	2,5	G 1/4" -19
RVM 40 -1 +15 H	40	-1...+15	2,5	G 1/4" -19

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.