# RVM 63

Vacuum pressure gauges without glycerine filling

## Properties

| | |
|---|---|
| **Design** | Pipe spring pressure gauge without glycerine filling |
| **Connection 1** | BSP external thread, cylindrical |
| **Sealing form 1** | flat seal with pin |
| **Connection** | at bottom |
| **Standard** | EN 837-1 |
| **Temp. range** | medium max. +60 °C<br>Ambient -20 °C to +60 °C |



## Note

Application range at idle load: 3/4 x full scale.
Application range with alternating load: 2/3 x full scale.

## Item

| Identification | Nominal size Ø | Scale range | Quality class | Connection |
|---|---|---|---|---|
| **RVM 63 -1 +0** | 63 | -1...0 | 2,5 | G 1/4" -19 |
| **RVM 63 -1 +0.6** | 63 | -1...+0,6 | 2,5 | G 1/4" -19 |
| **RVM 63 -1 +1.5** | 63 | -1...+1,5 | 2,5 | G 1/4" -19 |
| **RVM 63 -1 +3** | 63 | -1...+3 | 2,5 | G 1/4" -19 |
| **RVM 63 -1 +5** | 63 | -1...+5 | 2,5 | G 1/4" -19 |
| **RVM 63 -1 +9** | 63 | -1...+9 | 2,5 | G 1/4" -19 |
| **RVM 63 -1 +15** | 63 | -1...+15 | 2,5 | G 1/4" -19 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*