

RVM 63 H

Vacuum pressure gauges without glycerine filling

HANSA FLEX

Properties

| | |
|-----------------------|--|
| Design | Pipe spring pressure gauge without glycerine filling |
| Connection 1 | BSP external thread, cylindrical |
| Sealing form 1 | flat seal with pin |
| Connection | on back, centric |
| Standard | EN 837-1 |
| Temp. range | medium max. +60 °C Ambient -20 °C to +60 °C |



Note

Application range at idle load: 3/4 x full scale.

Application range with alternating load: 2/3 x full scale.

Item

| Identification | Nominal size Ø | Scale range | Quality class | Connection |
|------------------|----------------|-------------|---------------|------------|
| RVM 63 -1 +0 H | 63 | -1...0 | 2,5 | G 1/4" -19 |
| RVM 63 -1 +0.6 H | 63 | -1...+0,6 | 2,5 | G 1/4" -19 |
| RVM 63 -1 +1.5 H | 63 | -1...+1,5 | 2,5 | G 1/4" -19 |
| RVM 63 -1 +3 H | 63 | -1...+3 | 2,5 | G 1/4" -19 |
| RVM 63 -1 +5 H | 63 | -1...+5 | 2,5 | G 1/4" -19 |
| RVM 63 -1 +9 H | 63 | -1...+9 | 2,5 | G 1/4" -19 |
| RVM 63 -1 +15 H | 63 | -1...+15 | 2,5 | G 1/4" -19 |