

# BOE R

## Oil drain screw with valve

### Properties

<b>Connection 1</b>	BSP external thread, cylindrical
<b>Sealing form 1</b>	Shape A
<b>Connection 2</b>	metric cylindrical outer thread
<b>Design</b>	Drain valve
<b>Scope of supply</b>	with copper ring and cap
<b>Temp. min.</b>	-30 °C
<b>Temp. max.</b>	200 °C



### Note

Material for seal washer in protective cap: NBR.  
Seal material on valve seat: FPM (Viton)

### Description

The BOE oil drain screw is closed at rest (O-ring seal). When the oil drain hose is unscrewed, the valve is opened, allowing the oil to drain.

### Item

Identification	G1	G2	Material
BOE R 1/4	G 1/4" -19	M 22 x 1.5	Steel
BOE R 3/8	G 3/8" -19	M 22 x 1.5	Steel
BOE R 1/2	G 1/2" -14	M 26 x 1.5	Steel
BOE R 5/8	G 5/8" -14	M 26 x 1.5	Steel
BOE R 3/4	G 3/4" -14	M 26 x 1.5	Steel / brass
BOE R 7/8	G 7/8" -14	M 26 x 1.5	Steel / brass
BOE R 1	G 1" -11	M 26 x 1.5	Brass
BOE R 1 1/4	G 1.1/4" -11	M 26 x 1.5	Brass
BOE R 1 1/2	G 1.1/2" -11	M 26 x 1.5	Brass

### Accessories

BOE ABLASS	Oil drain hose
BOE ABLASS 90	Oil drain hose

### Spare parts

BOE DICHTSCHEIBE	Sealing washer for BOE drain screw
BOE KAPPE	Cap for drain screws