
BOE R
Oil drain screw with valve

Properties

Connection 1	BSP external thread, cylindrical
Sealing form 1	Shape A
Connection 2	metric cylindrical outer thread
Design	Drain valve
Scope of supply	with copper ring and cap
Temp. min.	-30 °C
Temp. max.	200 °C





Note

Material for seal washer in protective cap: NBR.
Seal material on valve seat: FPM (Viton)

Description

The BOE oil drain screw is closed at rest (O-ring seal). When the oil drain hose is unscrewed, the valve is opened, allowing the oil to drain.

Item

Identification	G1	G2	Material
BOE R 1/4	G 1/4" -19	M 22 x 1.5	Steel
BOE R 3/8	G 3/8" -19	M 22 x 1.5	Steel
BOE R 1/2	G 1/2" -14	M 26 x 1.5	Steel
BOE R 5/8	G 5/8" -14	M 26 x 1.5	Steel
BOE R 3/4	G 3/4" -14	M 26 x 1.5	Steel / brass
BOE R 7/8	G 7/8" -14	M 26 x 1.5	Steel / brass
BOE R 1	G 1" -11	M 26 x 1.5	Brass
BOE R 1 1/4	G 1.1/4" -11	M 26 x 1.5	Brass
BOE R 1 1/2	G 1.1/2" -11	M 26 x 1.5	Brass

Accessories

BOE ABLASS	Oil drain hose
BOE ABLASS 90	Oil drain hose

Spare parts

BOE DICHTSCHEIBE	Sealing washer for BOE drain screw
BOE KAPPE	Cap for drain screws

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.