


Properties

Connection 1	UN/UNF external threads
Sealing form 1	Shape A
Connection 2	metric cylindrical outer thread
Design	Drain valve
Scope of supply	with copper ring and cap
Temp. min.	-30 °C
Temp. max.	200 °C



Note

Material for seal washer in protective cap: NBR.

Seal material on valve seat: FPM (Viton)

Description

The BOE oil drain screw is closed at rest (O-ring seal). When the oil drain hose is unscrewed, the valve is opened, allowing the oil to drain.

Item

Identification	G1	G2	Material
BOE U 1/2-20	1/2"-20 UNF	M 22 x 1.5	Steel
BOE U 5/8-18	5/8"-18 UNF	M 22 x 1.5	Steel
BOE U 3/4-16	3/4"-16 UNF	M 26 x 1.5	Steel
BOE U 7/8-14	7/8"-14 UNF	M 26 x 1.5	Steel
BOE U 1-12	1" -12 UNF	M 26 x 1.5	Brass
BOE U 1 1/8-12	1.1/8"-12 UNF	M 26 x 1.5	Brass
BOE U 1 1/2-12	1.1/2"-12 UNF	M 26 x 1.5	Brass
BOE U 1 1/16-12	1.1/16"-12 UN	M 26 x 1.5	Brass

Accessories

BOE ABLOSS	Oil drain hose
BOE ABLOSS 90	Oil drain hose

Spare parts

BOE DICHTSCHEIBE	Sealing washer for BOE drain screw
BOE KAPPE	Cap for drain screws