

FK KG HR MG

Fixed coupling for fire brigade couplings

HANSA FLEX

Properties

Connection 1 BSP external thread, cylindrical

Sealing form 1 flat sealing

Connection 2 Claw coupling

Design Fixed coupling with outer thread

Sealing form 2 Moulded seal made of black nitrile

Material Brass



Item

Identification	Connecting thread	Cog space (mm)	Nominal size Storz
FK KG 31 HR 20 D MG	G 3/4" -14	31	25-D
FK KG 31 HR 25 D MG	G 1" -11	31	25-D
FK KG 44 HR 25 MG	G 1" -11	44	32
FK KG 44 HR 32 MG	G 1.1/4" -11	44	32
FK KG 52 HR 32 MG	G 1.1/4" -11	52	38
FK KG 52 HR 40 MG	G 1.1/2" -11	52	38
FK KG 66 HR 25 C MG	G 1" -11	66	52-C
FK KG 66 HR 32 C MG	G 1.1/4" -11	66	52-C
FK KG 66 HR 40 C MG	G 1.1/2" -11	66	52-C
FK KG 66 HR 50 C MG	G 2" -11	66	52-C
FK KG 66 HR 65 C MG	G 2.1/2" -11	66	52-C
FK KG 81 HR 50 MG	G 2" -11	81	65
FK KG 81 HR 65 MG	G 2.1/2" -11	81	65
FK KG 81 HR 75 MG	G 3" -11	81	65
FK KG 89 HR 50 B MG	G 2" -11	89	75-B
FK KG 89 HR 65 B MG	G 2.1/2" -11	89	75-B
FK KG 89 HR 75 B MG	G 3" -11	89	75-B
FK KG 133 HR 100 A MG	G 4" -11	133	110-A

Product versions

FK KG HR AL Fixed coupling for fire brigade couplings, Aluminium

Spare parts

DSD KG N Pressure suction seal for fire brigade couplings

DSD KG S Pressure suction seal, fire brigade coupling

DSD KG V Pressure suction seal, fire brigade coupling