


FK KG IR MG

Fixed coupling for fire brigade couplings

Properties

Connection 1	BSP cylindrical internal threads
Sealing form 1	flat sealing
Connection 2	Claw coupling
Design	Fixed coupling with inner thread
Sealing form 2	Moulded seal made of black nitrile
Material	Brass



Item

Identification	Connecting thread	Cog space (mm)	Nominal size Storz
FK KG 31 IR 13 D MG	G 1/2" -14	31	25-D
FK KG 31 IR 20 D MG	G 3/4" -14	31	25-D
FK KG 31 IR 25 D MG	G 1" -11	31	25-D
FK KG 66 IR 25 C MG	G 1" -11	66	52-C
FK KG 66 IR 32 C MG	G 1.1/4" -11	66	52-C
FK KG 66 IR 40 C MG	G 1.1/2" -11	66	52-C
FK KG 66 IR 50 C MG	G 2" -11	66	52-C
FK KG 66 IR 65 C MG	G 2.1/2" -11	66	52-C
FK KG 81 IR 50 MG	G 2" -11	81	65
FK KG 81 IR 65 MG	G 2.1/2" -11	81	65
FK KG 81 IR 75 MG	G 3" -11	81	65
FK KG 89 IR 50 B MG	G 2" -11	89	75-B
FK KG 89 IR 65 B MG	G 2.1/2" -11	89	75-B
FK KG 89 IR 75 B MG	G 3" -11	89	75-B
FK KG 133 IR 100 A MG	G 4" -11	133	110-A
FK KG 133 IR 110 A MG	G 4.1/2" -11	133	110-A

Product versions

FK KG IR AL Fixed coupling for fire brigade couplings, Aluminium

Spare parts

DSD KG N	Pressure suction seal for fire brigade couplings
DSD KG S	Pressure suction seal, fire brigade coupling
DSD KG V	Pressure suction seal, fire brigade coupling
FLD R N	Flat sealing ring for fire brigade couplings
FLD R N W	Flat sealing ring for fire brigade couplings
FLD R T	Flat sealing ring for fire brigade couplings