


KAMMRING G

Spacer diaphragm ring, imperial

Properties

Material Steel



Item

Identification	Ø d1 (mm)	Ø d2 (mm)	for thread	S (mm)
KAMMRING 1/8	12,20	15,00	G 1/8"	1,40
KAMMRING 1/4	16,15	19,50	G 1/4"	1,90
KAMMRING 3/8	19,50	23,50	G 3/8"	1,90
KAMMRING 1/2	23,30	28,50	G 1/2"	1,90
KAMMRING 3/4	28,60	34,50	G 3/4"	1,90
KAMMRING 1	36,60	43,50	G 1"	2,60
KAMMRING M42-11/4	44,90	55,50	G 1.1/4"	2,50
KAMMRING M48-11/2	50,90	62,00	G 1.1/2"	2,50
KAMMRING 2	63,30	70,00	G 2"	2,50

Accessory for following products

AOVR OK	Screw-in fitting
GE HROK AJ	Screw-in sockets
GE HROK AOB	Screw-in sockets
GE HROK L HJ	Screw-in socket, long
L HROK HB	Screw-in socket, L shaped
L HROK HJ	Screw-in socket, L shaped
L HROK HJOF	Screw-in socket, L shaped
T HROK HB	Screw-in socket, T shaped
T HROK HJ	Screw-in socket, T shaped
T HROK HJOF	Screw-in socket, T shaped
W45 HROK HB	Screw-in socket, angle 45°
W45 HROK HJ	Screw-in socket, angle 45°
W45 HROK HJOF	Screw-in socket, angle 45°
W90 HROK AOB	Screw-in socket, angle 90°
W90 HROK HB	Screw-in socket, angle 90°
W90 HROK HJ	Screw-in socket, angle 90°
W90 HROK HJL	Screw-in socket, angle 90°
W90 HROK HJOF	Screw-in socket, angle 90°
W90 HROK HJR	Screw-in socket, angle 90°
W90 HROK L HJ	Screw-in socket, long, angle 90°