

# LSK G

## Claw coupling (air)

### Properties

<b>Design</b>	Claw hose coupling
<b>Construction type</b>	with safety double cam
<b>Connection 1</b>	Hose connection
<b>Connection 2</b>	Claw coupling
<b>Sealing form 2</b>	Rubber sealing ring
<b>Standard</b>	DIN 3489
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	95 °C
<b>Material</b>	Cast iron
<b>Surface</b>	electro galvanised



### Item

Identification	for hose ID (mm)	Inches	Cog space (mm)	Operating pressure
LSK NW 06 G	6	1/4"	42	PN 10
LSK NW 10 G	10	3/8"	42	PN 10
LSK NW 13 G	13	1/2"	42	PN 10
LSK NW 15 G	15	5/8"	42	PN 10
LSK NW 19 G	19	3/4"	42	PN 10
LSK NW 25 G	25	1"	42	PN 10
LSK NW 32 G	32	1.1/4"	42	PN 10

### Product versions

LSK G AC	Claw coupling (air), Steel
----------	----------------------------

### Accessories

LSK GDOR	Rubber ring for claw coupling
----------	-------------------------------

### Spare parts

LSK GOOR	Rubber ring for claw coupling
----------	-------------------------------