

# LSK G

## Claw coupling (air)

### Properties

|                          |                        |
|--------------------------|------------------------|
| <b>Design</b>            | Claw hose coupling     |
| <b>Construction type</b> | with safety double cam |
| <b>Connection 1</b>      | Hose connection        |
| <b>Connection 2</b>      | Claw coupling          |
| <b>Sealing form 2</b>    | Rubber sealing ring    |
| <b>Standard</b>          | DIN 3489               |
| <b>Temp. min.</b>        | -40 °C                 |
| <b>Temp. max.</b>        | 95 °C                  |
| <b>Material</b>          | Cast iron              |
| <b>Surface</b>           | electro galvanised     |



### Item

| Identification | for hose ID<br>(mm) | Inches | Cog space<br>(mm) | Operating pressure |
|----------------|---------------------|--------|-------------------|--------------------|
| LSK NW 06 G    | 6                   | 1/4"   | 42                | PN 10              |
| LSK NW 10 G    | 10                  | 3/8"   | 42                | PN 10              |
| LSK NW 13 G    | 13                  | 1/2"   | 42                | PN 10              |
| LSK NW 15 G    | 15                  | 5/8"   | 42                | PN 10              |
| LSK NW 19 G    | 19                  | 3/4"   | 42                | PN 10              |
| LSK NW 25 G    | 25                  | 1"     | 42                | PN 10              |
| LSK NW 32 G    | 32                  | 1.1/4" | 42                | PN 10              |

### Product versions

|          |                            |
|----------|----------------------------|
| LSK G AC | Claw coupling (air), Steel |
|----------|----------------------------|

### Accessories

|          |                               |
|----------|-------------------------------|
| LSK GDOR | Rubber ring for claw coupling |
|----------|-------------------------------|

### Spare parts

|          |                               |
|----------|-------------------------------|
| LSK GOOR | Rubber ring for claw coupling |
|----------|-------------------------------|