# LSK G AC MODY

Claw coupling (air), MODY



| Properties     |                     |  |  |  |
|----------------|---------------------|--|--|--|
| Design         | MODY hose coupling  |  |  |  |
| Connection 1   | Hose connection     |  |  |  |
| Connection 2   | Claw coupling       |  |  |  |
| Sealing form 2 | Rubber sealing ring |  |  |  |
| Temp. min.     | -40 °C              |  |  |  |
| Temp. max.     | 95 °C               |  |  |  |
| Material       | Steel               |  |  |  |
| Surface        | electro galvanised  |  |  |  |



## Description

with reinforced thread protection ring and new sealing ring on both sides.

## Item

| Identification      | for hose ID<br>(mm) | Inches | Cog space<br>(mm) | Operating pressure |
|---------------------|---------------------|--------|-------------------|--------------------|
| LSK NW 13 G AC MODY | 12,5                | 1/2"   | 42                | PN 16              |
| LSK NW 20 G AC MODY | 20,0                | 3/4"   | 42                | PN 16              |
| LSK NW 25 G AC MODY | 25,0                | 1"     | 42                | PN 16              |

### Accessories

LSK SDOR N Rubber ring for MODY coupling

### Spare parts

LSK SGOR N Rubber ring for MODY coupling