

LSK IR G

Claw coupling (air)

Properties

| | |
|--------------------------|----------------------------------|
| Design | Claw inner thread coupling |
| Construction type | with safety double cam |
| Connection 1 | BSP cylindrical internal threads |
| Connection 2 | Claw coupling |
| Sealing form 2 | Rubber sealing ring |
| Standard | DIN 3489 |
| Temp. min. | -40 °C |
| Temp. max. | 95 °C |
| Material | Cast iron |
| Surface | electro galvanised |



Item

| Identification | Connecting thread | Cog space (mm) | Operating pressure |
|----------------|-------------------|----------------|--------------------|
| LSK NW 06 IR G | G 1/4" -19 | 42 | PN 10 |
| LSK NW 10 IR G | G 3/8" -19 | 42 | PN 10 |
| LSK NW 13 IR G | G 1/2" -14 | 42 | PN 10 |
| LSK NW 20 IR G | G 3/4" -14 | 42 | PN 10 |
| LSK NW 25 IR G | G 1" -11 | 42 | PN 10 |
| LSK NW 32 IR G | G 1.1/4" -11 | 42 | PN 10 |

Product versions

LSK IR G AC Claw coupling (air), Steel

Accessories

LSK GDOR Rubber ring for claw coupling

Spare parts

LSK GOOR Rubber ring for claw coupling