

# LSK IR G

## Claw coupling (air)

### Properties

<b>Design</b>	Claw inner thread coupling
<b>Construction type</b>	with safety double cam
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Connection 2</b>	Claw coupling
<b>Sealing form 2</b>	Rubber sealing ring
<b>Standard</b>	DIN 3489
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	95 °C
<b>Material</b>	Cast iron
<b>Surface</b>	electro galvanised



### Item

Identification	Connecting thread	Cog space (mm)	Operating pressure
LSK NW 06 IR G	G 1/4" -19	42	PN 10
LSK NW 10 IR G	G 3/8" -19	42	PN 10
LSK NW 13 IR G	G 1/2" -14	42	PN 10
LSK NW 20 IR G	G 3/4" -14	42	PN 10
LSK NW 25 IR G	G 1" -11	42	PN 10
LSK NW 32 IR G	G 1.1/4" -11	42	PN 10

### Product versions

LSK IR G AC	Claw coupling (air), Steel
-------------	----------------------------

### Accessories

LSK GDOR	Rubber ring for claw coupling
----------	-------------------------------

### Spare parts

LSK GOOR	Rubber ring for claw coupling
----------	-------------------------------