

# LSK IR G AC

Claw coupling (air)

**HANSA FLEX**

## Properties

<b>Design</b>	Claw inner thread coupling
<b>Construction type</b>	with safety double cam
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Connection 2</b>	Claw coupling
<b>Sealing form 2</b>	Rubber sealing ring
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	95 °C
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Connecting thread	Cog space (mm)	Operating pressure
LSK NW 10 IR G AC	G 3/8" -19	42	PN 10
LSK NW 13 IR G AC	G 1/2" -14	42	PN 10
LSK NW 16 IR G AC	G 5/8" -14	42	PN 10
LSK NW 20 IR G AC	G 3/4" -14	42	PN 10
LSK NW 25 IR G AC	G 1" -11	42	PN 10

## Product versions

<b>LSK G</b>	Claw coupling (air), Cast iron
--------------	--------------------------------

## Accessories

<b>LSK GDOR</b>	Rubber ring for claw coupling
-----------------	-------------------------------

## Spare parts

<b>LSK GOOR</b>	Rubber ring for claw coupling
-----------------	-------------------------------