# LSK M
Claw coupling (air)

## Properties

| | |
|---|---|
| **Design** | Claw hose coupling |
| **Construction type** | with safety double cam |
| **Connection 1** | Hose connection |
| **Connection 2** | Claw coupling |
| **Sealing form 2** | Brass seal with rubber insert |
| **Temp. min.** | -40 °C |
| **Temp. max.** | 95 °C |
| **Material** | Cast iron |
| **Surface** | galvanised, white chromised |



## Note

A coupling with rubber seal must be used as the counter coupling.

## Item

| Identification | for hose ID (mm) | Inches | Cog space (mm) | Operating pressure |
|---|---|---|---|---|
| **LSK NW 13 M** | 13 | 1/2" | 42 | PN 10 |
| **LSK NW 15 M** | 15 | 5/8" | 42 | PN 10 |
| **LSK NW 19 M** | 19 | 3/4" | 42 | PN 10 |
| **LSK NW 25 M** | 25 | 1/2" | 42 | PN 10 |

## Spare parts

| | |
|---|---|
| **LSK HOOS** | Retaining screw for claw coupling |
| **LSK MOOH** | Brass sleeve for claw coupling |
| **LSK SOOR** | Hose ring for claw coupling |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*